

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 March 2005 (24.03.2005)

PCT

(10) International Publication Number
WO 2005/027085 A1

(51) International Patent Classification⁷: **G09G 3/30**

[JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd.,
398, Hase, Atsugi-shi, Kanagawa 2430036 (JP).

(21) International Application Number:
PCT/JP2004/013381

(22) International Filing Date:
6 September 2004 (06.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-321613 12 September 2003 (12.09.2003) JP

(71) Applicant (for all designated States except US): **SEMI-
CONDUCTOR ENERGY LABORATORY CO., LTD.**
[JP/JP]; 398, Hase, Atsugi-shi, Kanagawa 2430036 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **KIMURA, Hajime**

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: SEMICONDUCTOR DEVICE AND DRIVING METHOD OF THE SAME



(57) Abstract: In the case of reducing an effect of variations in current characteristics of transistors by inputting a signal current to a transistor in a pixel, a potential of a wiring is detected by using a precharge circuit. In the case where there is a difference between a predetermined potential and the potential of the wiring, a charge is supplied to the wiring to perform a precharge by charging rapidly. When the potential of the wiring reaches the predetermined potential, the supply of charge is stopped and a signal current only is supplied. Thus, a precharge is performed only in a period until the potential of the wiring reaches the predetermined potential, therefore, a precharge can be performed for an optimal period.

WO 2005/027085 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*